

Material Safety Data Sheet

BLUE OX™ 901 - Polyurethane Adhesive

ADHESIVE®



TELEPHONE 715-832-4557

1. Product Information

Product Name BX901-B
Proper Shipping Name NA
Product Class Polyol
U.S.D.O.T. Hazard Class NA
U.S.D.O.T. Hazard Number NA
U.S.D.O.T. Label None
HMIS CODES: Health 1 Flammability 1 Reactivity 0
Hazard Ratings: 4 = Severe 3 = Serious 2 = Moderate 1 = Slight 0 = Minimal

2. Hazardous Ingredients

Ingredients	CAS#	TLV**	Percent*
NJTSRN-BX901-B	-	-	-

*Major = Over 25%, Minor = 6%-25%, Trace = Under 6%, Residue = Unknown % Residue Possible

**TLV as established by ACGIH and or OSHA Standard

*** If no components are listed then this material contains non-hazardous substances according to 29CFR1910.1200.

3. Physical and Chemical Properties

Physical State Liquid
Color White
Solubility Negligible
LBS/Gallon 11.75
Vapor Density Heavier than air
Boiling Point NA
Liquid Density Lighter than water

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guarantee analysis of any specific lot or as specifications for the product.

4. Fire and Explosion Data

Flash Point >325°F (PMCC)
Flammability Limits UEL % Not established
Extinguishing Media: Foam, CO2, Dry Chemical, Water Fog
Special Fire Fighting Procedures For large fires, alcohol resistant foams(ATC type) are preferred if available. General purpose synthetic foams(including AFFF) or protein foams may function but much less effectively. Water is not recommended but may be applied in very large quantities as a fine spray when other extinguishing media are not available.
Unusual Fire and Explosion Hazards Full emergency equipment with self-contained breathing apparatus should be worn. During a fire irritating, toxic gases (see Reactive Data) and smoke are present from decomposition/combustion. Product reacts with water. Reaction may produce heat and/or gases.

5. Health Hazards Data

Effects of Over Exposure **Acute**
Eyes: Can cause eye irritation.
Skin: Can cause skin irritation. Repeated or prolonged exposure may cause sensitization. Acute:- Isocyanates reacts with skin protein & moisture & cause irritation which may include reddening, swelling, rash, scaling or blistering.
Ingestion: May cause nausea, vomiting or other signs of illness.
Inhalation: MDI vapors at concentrations above TLV can irritate the mucous membranes in the respiratory Tract (nose, throat, lungs) causing a runny nose, soar throat, coughing, chest discomfort, shortness of breath and reduced lung function. Persons with pre-existing , nonspecific bronchial hyperreactivity can respond to concentrations below TLV with similar systems as well as asthma attack. Overexposure to isocyanates has also been reported to cause lung damage (including decrease in lung function) which may be permanent.

6. First Aid Procedures

Eye Contact Flush immediately with clean, lukewarm water (low pressure) for at least 15 minutes while holding eye lids open. Obtain medical attention immediately.
Skin Contact Remove contaminated clothing. Wash affected areas thoroughly with soap and water, warm water is preferable if readily available. Wash contaminated clothing before reuse. Contact physician if irritation occurs.
Inhalation Move to fresh air. Administer oxygen or artificial respiration as needed. Obtain medical attention. Asthmatic -type symptoms may develop and may be immediate or delayed up to several hours.
Ingestion Do not give any liquids (do not induce vomiting). Get medical help immediately. Give 1 to 2 cups of milk or water to drink. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
CONSULT PHYSICIAN IMMEDIATELY.

7. Special Protection Information.

Eye Protection	Liquid chemical goggles or full-face shield.
Skin Protection	Chemical resistant gloves (natural latex and neoprene recommended). Cover as much of the exposed skin area as possible with appropriate clothing. If skin creams are used, keep the area covered by the cream to a minimum.
Ventilation and Respiratory Protection	Exhaust ventilation sufficient to keep airborne concentrations of the hazardous constituents below TLV or other appropriate exposure limit must be utilized. When respiratory protection is required for certain operations, use an approved positive-pressure supplied – air respirator. Avoid breathing vapors which may be produced under some conditions such as heating. Avoid breathing aerosols and mists. Use NIOSH/MSHA approved respiratory protection equipment when airborne exposure is excessive. Observe OSHA regulations for respirator use (29 CFR 1910.134)
Other	Safety showers and eye wash stations should be easily accessible to the work area. <i>Worker training is important. Follow all label precautions.</i>

8. Reactivity Data

Stability	STABLE UNDER NORMAL STORAGE, POLYMERIZATION WILL NOT OCCUR. Product is VERY UNSTABLE when contaminated with water.
Conditions to Avoid	Avoid temperatures above 86°F. Avoid temperatures below 64°F. Avoid moisture. Product can decompose at elevated temperature.
Materials to Avoid	Avoid water.
Hazardous Polymerization	Will not occur under normal conditions.
Decomposition Products	By heat and fire: Carbon dioxide, carbon monoxide, Aldehydes, acids and other organic substances may be formed.

9. Spill, Leak and Disposal Procedures

Action to be taken if material is released or spilled	Remove all sources of ignition. Avoid contact with material. Ventilate the area. Equip clean-up crew with appropriate protective equipment. Persons not wearing proper protective equipment should be excluded from the area until cleanup is complete. Dike or impound spilled material and control further spillage if feasible. Notify appropriate authorities if necessary. Cover spill area with sawdust, vermiculite, or other absorbent material; collect material in open containers. Attempt to neutralize by adding a mixture of: water(80%), with non-ionic surfactant Tergitol TMN-10 (20%), or water (90%), concentrated ammonia (3-8%) and detergent (2%). Add about 10 parts of neutralizer per part of Isocyanate while mixing. Allow to stand uncover for 48 hours to let CO2 escape. If ammonia is used, use good ventilation to prevent vapor exposure. Large quantities may be pumped into closed, but not sealed containers. Refer to section IX for disposal information. Remove containers to safe place and cover.
Waste Disposal Method	Dispose of waste in accordance with Federal, State, and Local regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch.

10. Special Precautions and Storage Data

Contact	Avoid skin and eye contact. Avoid breathing vapor, mist of fumes. Ensure that all containers are properly labeled to prevent accidental ingestion or improper disposal. Reseal partly used containers. Wash with soap and water before eating, drinking or using toilet facilities. Store under cool, dry conditions away from open flames and high temperatures. Observe conditions of good industrial hygiene and safe working practice.
Storage	Store indoors in a dry place away from heat between the temperatures 64 to 86°F. Keep containers tightly closed when not in use. Keep product from exposing to atmospheric moisture and maintain a nitrogen atmosphere in the containers at all times. Do not store product contaminated with water to prevent potential hazardous reaction. Refer to section VIII of the MSDS for Reactivity and Stability data.

11. Regulatory Information

TSCA	All components of this product are registered under the regulations of the Toxic Substance Control Act.
SARA TITLE III	Section 302 Extremely Hazardous Substance: None

We believe the information contained herein is current and accurate as of this date of this Material Safety Data Sheet. Since the use of this information and these opinions and the conditions of use of this product are not under the control of ADHESIVE R&D[®], Inc. or its agents or distributors, it is the user's obligation to determine the conditions of safe use of this product. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. ADHESIVE R&D[®], Inc. warrants that the product conforms with ADHESIVE R&D[®]'s written specifications, and is free from defects and disclaims all other warranties, expressed or implied and is not responsible for loss claim of damages resulting from the use of its products.

Rev 01/03