



# NICKEL GUARD PREMIUM™

NICKEL GUARD PREMIUM

Nickel, aluminum, and graphite are blended into a high performance lithium complex grease, providing protection up to 2600°F. **NICKEL GUARD PREMIUM™** is used where copper can not be present, and maximum protection is required. Because of the hardness of the nickel particle, **NICKEL GUARD PREMIUM™** performs particularly well when surfaces are under extreme pressure. It is the preferred product when working with high alloy steels, or very dissimilar metals. The burr-like shape of the nickel particle makes it the recommended anti-seize for preventing galling when assembling stainless steel fasteners, fittings or pipe.

## PHYSICAL PROPERTIES

Color	Silver Gray
Specific Gravity	1.2
Weight per Gallon	10.0 lbs.
Penetration	270±10
Drop Point	380°
Flash Point: C.O.C.	440°F
Particle Size	0.5 Mil Maximum
Coefficient of Friction	.08 (Shell 4 Ball Method)

We believe the information contained herein is current and accurate as of this date of this Technical Data Sheet. Since the use of this information and these opinions and the conditions of use of this product are not under the control of ANTI-SEIZE R&D, Inc. or its agents or distributors, it is the user's obligation to determine the conditions of safe use of this product. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. ANTI-SEIZE R&D, Inc. warrants that the product conforms with ANTI-SEIZE R&D, Inc.'s written specifications, and is free from defects and disclaims all other warranties, expressed or implied and is not responsible for loss claim of damages resulting from the use of its products.

Rev 01/03